

TADANO FAUN

ATF 60-4




PERUSPUOMI

DIN/ISO

→ m	10.4 m	17.8 m	17.8 m	17.8 m	25.3 m	25.3 m	25.3 m	32.7 m	32.7 m	36.5 m	40.2 m
2.5	60.0**										
3.0	50.0										
3.5	44.8	20.0	30.0	13.0							
4.0	41.0	20.0	29.0	13.0							
4.5	37.0	20.0	27.5	13.0							
5.0	34.3	20.0	26.2	13.0	13.0	17.0	11.8				
6.0	29.8	20.0	22.6	13.0	13.0	17.0	11.8	13.0	9.5		
7.0	25.3	20.0	19.8	13.0	13.0	15.8	11.8	13.0	9.2		
8.0	16.9	20.0	17.5	13.0	13.0	14.5	11.8	13.0	8.8	9.0	7.0
9.0		18.4	15.6	13.0	13.0	13.3	11.4	12.0	8.5	8.8	7.0
10.0		15.5	14.1	13.0	13.0	12.0	11.0	11.0	8.1	8.5	7.0
11.0		13.2	12.5	13.0	12.6	10.9	10.5	10.1	7.7	8.3	7.0
12.0		11.4	10.8	12.6	12.1	9.8	10.1	9.2	7.4	8.1	7.0
14.0		8.8	8.2	9.9	9.8	8.2	8.8	7.8	6.7	7.6	6.5
16.0					7.8	6.6	7.7	6.7	5.8	6.5	6.1
18.0					6.3	5.1	6.8	5.8	5.1	5.6	5.3
20.0					5.2	4.0	5.8	4.8	4.5	4.9	4.6
22.0					4.3	3.1	4.9	3.9	4.0	4.1	4.1
24.0								3.2	3.6	3.3	3.6
26.0								2.6	3.2	2.7	3.0
28.0								2.1	2.9	2.2	2.5
30.0								1.6	2.7	1.8	2.0
32.0										1.5	1.7
34.0										1.1	1.4
36.0											1.1



I	0	50	100	0	50	100	0	100	0	100	100
II	0	50	0	33	50	100	67	100	100	100	100
III	0	0	0	33	50	0	67	50	100	75	100
IV	0	0	0	33	50	0	67	50	100	75	100



RISTIKKOJATKE

DIN/ISO

→ m	36.5 m + 9.0 m			40.2 m + 9.0 m			40.2 m + 16.0 m		
	5°	17°	30°	5°	17°	30°	5°	17°	30°
10.0	4.80			3.80					
11.0	4.80			3.80					
12.0	4.80	4.00	3.00	3.80	3.40		2.20		
14.0	4.60	3.75	2.85	3.80	3.40	2.80	2.20	1.80	
16.0	4.40	3.45	2.65	3.70	3.25	2.70	2.20	1.80	1.30
18.0	4.20	3.15	2.50	3.55	3.10	2.55	2.15	1.75	1.30
20.0	3.75	2.90	2.35	3.45	3.00	2.45	2.05	1.65	1.25
22.0	3.40	2.70	2.25	3.30	2.85	2.35	2.00	1.60	1.25
24.0	3.10	2.55	2.15	3.20	2.70	2.25	1.90	1.50	1.20
26.0	2.85	2.40	2.05	2.80	2.55	2.15	1.85	1.45	1.15
28.0	2.35	2.25	1.95	2.40	2.40	2.05	1.70	1.35	1.15
30.0	1.85	2.00	1.90	1.95	2.10	1.95	1.55	1.30	1.10
32.0	1.50	1.60	1.70	1.60	1.70	1.80	1.45	1.25	1.05
34.0	1.15	1.25	1.30	1.25	1.35	1.45	1.35	1.15	1.00
36.0	0.85	0.90	0.95	0.95	1.05	1.10	1.30	1.10	1.00
38.0	0.60	0.65	0.65	0.70	0.75	0.80	1.15	1.05	0.95
40.0		0.40	0.40	0.45	0.50	0.55	0.90	1.00	0.90
42.0							0.75	0.85	0.90
44.0							0.55	0.65	0.75
46.0								0.45	0.50




I	100			100			100		
II	100			100			100		
III	75			100			100		
IV	75			100			100		

ATF 80-4

Nostoarvot / korkeudet
maksimivastapainoin.

Kokonaispaino ajovarusteisena 48 tonnia
Maksimijonopeus 80 km/h



DIN/ISO

